

SAFETY DATA SHEET

T-CUT COLOUR FAST WHITE 500ML

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME: T-CUT COLOUR FAST WHITE 500ML

PART No.: CMW001

SUPPLIER: TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
Tel: 0161 764 5981
Fax: 0161 797 5899

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME			CONTENT
CAS No.:	EINECS Nr.:	CLASSIFICATION	
PETROLEUM DISTILLATES (SOLVENT NAPHTHA B)			1-5 %
64742-95-6	265-199-0	Xn ,N R-10, 51/53, 65	
1,2,4-TRIMETHYLBENZENE			1-5 %
95-63-6	202-436-9	Xn ,N R-10, 20, 36/37/38, 51/53	
MESITYLENE			0-1 %
108-67-8	203-604-4	Xi ,N R-10, 37, 51/53	
PROPYLBENZENE			0-1 %
98-82-8	202-704-5	Xn ,N R-10, 37, 51/53, 65	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; Kerosine - UNSPECIFIED			5-10 %
64742-47-8	265-149-8	Xn R-65	

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION:	NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.
SKIN:	Remove affected person from source of contamination. Get medical attention if irritation persists after washing.
EYES:	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:	This material is not flammable. Use extinguishing media appropriate for surrounding fire.
-----------------------------	---

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS:	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.
-------------------------------	---

7. HANDLING AND STORAGE

USAGE PRECAUTIONS:	Avoid spilling, skin and eye contact.
STORAGE PRECAUTIONS:	Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
PROPYLBENZENE	98-82-8	OES	25 ppm(Sk)	50 ppm(Sk)

INGREDIENT COMMENTS: OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

PROTECTIVE EQUIPMENT:



VENTILATION:	Provide adequate general and local exhaust ventilation.
PROTECTIVE GLOVES:	Use suitable protective gloves if risk of skin contact.
EYE PROTECTION:	If risk of splashing, wear safety goggles or face shield.
OTHER PROTECTION:	Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENIC WORK PRACTICES: DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Liquid.		
COLOUR:	White.		
DENSITY/SPECIFIC GRAVITY (g/ml):	1.050 - 1.070	Temperature (°C):	20
pH-VALUE, CONC. SOLUTION:	7.5 - 9.5		
VISCOSITY (interval):	4000 - 8000 cps	Temperature (°C):	20

10. STABILITY AND REACTIVITY

STABILITY: Normally stable.

CONDITIONS TO AVOID: Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMP. PRODUCTS: Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

HEALTH WARNINGS: No specific health warnings noted.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION

UN No. ROAD:	N/A
UK ROAD TRANSPORT CLASS:	N/A
UK ROAD PACK GR.:	N/A
ADR CLASS No.:	N/A
ADR CLASS:	Not classified for transportation.
PROPER SHIPPING NAME I:	N/A
IMDG CLASS:	N/A
IMDG PACK GR.:	N/A
ICAO CLASS:	N/A
AIR PACK GR.:	N/A

15. REGULATORY INFORMATION

RISK PHRASES:	R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SAFETY PHRASES:	S-56 Dispose of this material and its container to hazardous or special waste collection point.
STATUTORY INSTRUMENTS:	Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

INFORMATION SOURCES:	Dangerous Properties of Industrial Materials Report, N.Sax et.al.
ISSUED BY:	PJC
REVISION DATE:	2001-12-05
REV. No./REPL. SDS GENERATED:	1
SDS No.:	200245
R-PHRASES (Full Text):	R-65 Harmful: may cause lung damage if swallowed. R-10 Flammable. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-20 Harmful by inhalation. R-36/37/38 Irritating to eyes, respiratory system and skin. R-37 Irritating to respiratory system.
DISCLAIMER:	The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to

the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.